

SP20HA


Sound Projector

Features

- Weatherproof
- Made out of white ABS housing
- Fitted with broadband loudspeaker
- 75 cm connection cable
- Aluminium grill
- Adjustable power tapping
- IP 56

▶ Applications

- Wide variation of in- and outdoor applications
- Shoppingstreets
- Factory halls
- Amusement parks
- Playgrounds



It features a 5" full range speaker with a built-in 100V line transformer.

The power can be set in 4 adjustable steps of impedance:

- 10 Watt @ 100V
- 5 Watt @ 100V
- 2,5 Watt @ 100V
- 1,25 Watt @ 100V

The enclosure is made of white weatherproof ABS with a white aluminium front grill and a special weatherproof coating.

The connection and mounting of the speaker can be done by the standard attached 75 cm connection cable which has a waterproof cable gland.



▶ Specifications

- 1		
SYSTEM SPECIFICATIONS		
Speaker Type		Broadband
Max Power		20 W
RMS Power		10 W
Impedance		8 Ohm
Line Transformer Taps	1	10 W / 1k Ohm
	2	5 W / 2k Ohm
	3	2,5 W / 4k Ohm
	4	1,25 W / 8k Ohm
Sensitivity (1W/1m)		92 dB
Sound Pressure (Max W/1m)		104 dB
Frequency Response (± 3 dB)		130 Hz - 15 kHz
Horizontal Dispersion		180°
Vertical Dispersion		180°
IP Rating (Ingress Protection)		IP 56
PRODUCT FEATURES		
Dimensions (Diameter x Depth)		Ø 138 x 204 mm
Weight Net		1,9 Kg
Driver		5"
Construction		ABS housing
Grill Type		Aluminium grill
Connection		75 cm connection cable
Available Colour		White (RAL9010)
SHIPPING & ORDERING		
Packaging		Carton box
Shipping Weight & Volume		2,5 Kg

*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products