



## Versatile Portable Projector with High Brightness

### FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 4000 lumens of brightness and 20,000:1 contrast ratio for clear, crisp and bright presentations
- WXGA (1280 x 800) native resolution scalable up to a maximum WUXGA (1920 x 1200) resolution
- Dual-HDMI inputs for high definition content with the same high quality
- Compact and lightweight at 2.6kg for easy portability
- A long lamp life up to 10,000 hours for low Total Cost of Ownership (TCO)
- Audio ready with built-in 2 watt audio speaker, audio-in and audio-out ports



## From meeting room to presentations anywhere on the road

The DW275 is a native WXGA digital projector from Vivitek. It features DLP® and BrilliantColor™ technologies to display distinct, vibrant images in a widescreen format. The Vivitek DW275 features numerous connectivity options including two HDMI v1.4, a brightness level of 4000 Lumens and a 20,000:1 contrast ratio. With its light weight and compact form, the DW275 projector is easy to install and will fit into any budget.



## DW275 SPECIFICATIONS

Image	<b>Display Type</b>	Single chip DLP® Technology by Texas Instruments
	<b>Brightness</b>	4000 ANSI Lumens
	<b>Native Resolution</b>	WXGA (1280 x 800)
	<b>Max. Supported Resolution</b>	WUXGA (1920 x1200) @60Hz
	<b>Contrast Ratio</b>	20,000:1
	<b>Native Aspect Ratio</b>	16:10
	<b>Keystone Correction</b>	Vertical: +/-40°
Optical	<b>Throw Ratio</b>	1.55 - 1.86 : 1
	<b>Image Size (Diagonal)</b>	40" - 300"
	<b>Projection Distance</b>	1.3m -10.2m
	<b>Projection Lens</b>	F = 2.42 - 2.62, f = 22.5 - 25.79 mm
	<b>Zoom Ratio</b>	1.2x
	<b>Offset</b>	1,04
Features	<b>Features</b>	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential)
Connectivity	<b>I/O Connection Ports</b>	VGA-In (15pin D-Sub) (x2), HDMI Number of Ports 1.4b (x2), S-Video, Composite Video, Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RS-232, USB miniB (Service)
General	<b>Lamp Life and Type</b>	5,500 / 7,000 / 10,000 Hours (Normal / Eco. / Dynamic Eco. Mode), 210W
	<b>Speakers</b>	2W
	<b>Dimensions (W x D x H)</b>	331 x 244 x 105 mm
	<b>Weight</b>	2.6 kg
	<b>Noise Level</b>	29dB Eco. Mode
	<b>Power</b>	Supply: AC 100-240V, 50/60Hz Consumption: 210W (Eco. Mode), 250W (Normal Mode), <0.5W (Standby)
	<b>Warranty</b>	Entry Warranty: 2 years projector / 1 year on lamp or 1.000 hours whichever comes first, Education Warranty: 5 years projector / 3 years on lamp or 2.000 hours whichever comes first
	<b>Standard Accessories</b>	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
<b>Optional Accessories</b>	Spare Lamp P/N (XX5810005600 ), Remote Control P/N (XX5040005400), Carrying Case P/N (XX3520000800)	